



Features

- High Current Capability
- Low Forward Voltage Drop

Mechanical Data

- Flat Lead SOD-123 Small Outline Plastic Package
- Polarity: Color band denotes cathode end
- Mounting Position: Any

Marking: 1N5817W: SJ

1N5818W: SK

1N5819W: SL

Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.450	0.650	0.018	0.026
c	0.080	0.150	0.003	0.006
D	1.500	1.700	0.059	0.067
E	2.600	2.800	0.102	0.110
E1	3.550	3.850	0.140	0.152
L	0.500 REF		0.020 REF	
L1	0.250	0.450	0.010	0.018
θ	0°	8°	0°	8°

Maximum Ratings & Thermal Characteristics (Ratings at 25 °C ambient temperature unless otherwise specified.)

Parameters	Symbol	1N5817W	1N5818W	1N5819W	Unit
Maximum repetitive peak reverse voltage	VRRM	20	30	40	V
Maximum RMS voltage	VRMS	14	21	28	V
Maximum DC blocking voltage	VDC	20	30	40	V
Maximum average forward rectified current	IFM		1.0		A
Peak forward surge current 8.3 ms single half sine-wave	IFSM		9		A
Typical thermal resistance	R _{θJA}		250		/W
Power Dissipation	PD		500		mW
Storage temperature range	TSTG		-50-+150		

Electrical Characteristics (Ratings at 25 °C ambient temperature unless otherwise specified).

Parameters	Symbol	Test conditions	1N5817W	1N5818W	1N5819W	Unit
Maximum forward voltage	VF	IF = 1.0A IF = 3.0A	0.450 0.750	0.550 0.875	0.600 0.900	V
Maximum reverse breakdown voltage	VR	IR=1mA	20	30	40	V
Maximum reverse current	IR	VR=20V 1N5817W VR=30V 1N5818W VR=40V 1N5819W		1.0		mA
Type junction capacitance	C _j	VR = 4.0V, f = 1MHz		120		pF

Characteristic Curves

